

AGE

HIDROCARBUROS | PETROL

Descripción

Gassoflex AGE es recomendada para la impulsión y/o aspiración de carburantes, aceites y lubricantes tanto en camiones cisternas, vagones o en planta, pero gracias a la combinación de sus espirales en aluminio y acero galvanizado es significativamente mas ligera, haciendo posible su uso incluso en aplicaciones marinas de grandes diámetros

Construcción

- Espiral interior: Aluminio (A)
- Espiral exterior: Acero Galvanizado (G)
- Forro interior: Polipropileno (E)
- Cubierta: Tejido Poliester / PVC

Características

- Normas: EN 13765:2018
- Gama temperatura: -30 °C a +100 °C
- Factor seguridad: 5:1
- Vacío: 0,9 bar
- Longitud rollos: 30 m. Otra consultar.

Description

Gassoflex AGE is recommended for the delivery and / or suction of fuels, oils and lubricants in tank trucks, wagons or in plant, but thanks to the combination of its spirals in aluminum and galvanized steel is significantly lighter, making it possible to use even in marine applications with large diameters

Construction

- Inner Wire spiral: Aluminum (A)
- Outer Wire spiral: Galvanized Steel (G)
- Inner Lining: Polypropylene (E)
- Cover: PVC Coated Polyester Cloth

Features

- Norms: EN 13765:2018
- Temperature range: -30 °C a +100 °C
- Safety factor: 5:1
- Vacuum: 0,9 bar
- Length coils: 30 m. Other under request.



Datos técnicos / Technical data

AGE	STANDARD DUTY							MARINE OR HEAVY DUTY			
	IN D	Ø in	1	1 1/2	2	2 1/2	3	4	6	8	10
BR	∅	mm			150	190	240	320			
W	⚖	Kg/m			0,90	1,20	1,80	2,94			
CODE	⊙	10 bar/ 145 psi			●	●	●	●			