

HOSE TOWER

PRODUCTOS QUÍMICOS | CHEMICAL

Descripción

Gassoflex HOSE TOWER es una manguera que ha sido desarrollada con una combinación especial de sus espirales y refuerzos internos para dotarla de una resistencia extra a la elongación a la que se ve sometida por su aplicación en los estructuras de carga de buques en las terminales portuarias.

Construcción

- Espiral interior: Acero / Inox / PP
- Espiral exterior: Acero / Inox / PP
- Forro interior: PP / PTFE
- Cubierta: Tejido Poliester / PVC

Características

- Normas: EN 13765:2018
- Gama temperatura: -30 °C a +100 °C
- Factor seguridad: 5:1
- Vacío: 0,9 bar
- Longitud rollos: 30 m. Otra consultar.

Description

Gassoflex HOSE TOWER is a hose that has been developed with a special combination of its internal spirals and reinforcements to give it an extra resistance to the elongation to which it is subjected by its application in the load structures of vessels at port terminals.

Construction


- Inner Wire spiral: SS / CS / PP Coated Steel
- Outer Wire spiral: SS / CS / PP Coated Steel
- Inner Lining: PP/ PTFE
- Cover: PVC Coated Polyester Cloth

Features

- Norms: EN 13765:2018
- Temperature range: -30 °C a +100 °C
- Safety factor: 5:1
- Vacuum: 0,9 bar
- Length coils: 30 m. Other under request.



Datos técnicos / Technical data

HOSE TOWER	STANDARD DUTY							MARINE OR HEAVY DUTY 			
	IN D	Ø in	1	1 1/2	2	2 1/2	3	4	6	8	10*
BR	⌀	mm							497	740	920
W	⬇	Kg/m							12,40	22,30	25,90
CODE	⊙	14 bar/ 203 psi							•	•	•
CODE	⊙	21 bar/ 315 psi **									

* Máx. 28 m ** 21 bar WP También disponible bajo demanda. Also available on request.