

QX Four Spiral Hose (*Half Bend*)

Meets or exceeds the requirements of SAE 100R12 - EN856
(Half the bend radius of SAE100R12)



- Tube: Nitrile
- Reinforcement: Four spirals of high tensile wire
- Cover: Black, oil, abrasion and weather resistant synthetic rubber, MSHA approved
- Temperature: -40°C to +121°C (-40°F to +250°F)
- Packaging: Coils
- Application: Locations that require greater flexibility.

| PART NUMBER | HOSE I.D. | | HOSE O.D. | | MAXIMUM WORKING PRESSURE (psi) | MINIMUM BURST PRESSURE (psi) | MINIMUM BEND RADIUS | | WEIGHT (lbs/ft) | ONE PIECE Non-Skive |
|-------------|-----------|------|-----------|------|--------------------------------|------------------------------|---------------------|------|-----------------|---------------------|
| | (in) | (mm) | (in) | (mm) | | | (in) | (mm) | | COUPLINGS |
| QX-06 | 3/8 | 19.2 | 0.76 | 19.2 | 4,060 | 16,240 | 2.6 | 65 | .40 | N, V |
| QX-08 | 1/2 | 22.6 | 0.89 | 22.6 | 4,060 | 16,240 | 3.5 | 90 | .54 | N, V |
| QX-10 | 5/8 | 26.8 | 1.06 | 26.8 | 4,060 | 16,240 | 3.9 | 100 | .74 | N |
| QX-12 | 3/4 | 30.4 | 1.20 | 30.4 | 4,060 | 16,240 | 4.7 | 120 | .94 | N, V |
| QX-16 | 1 | 38.1 | 1.50 | 38.1 | 4,060 | 16,240 | 5.9 | 150 | 1.34 | N |