

DOCK OIL TRANSFER HOSE/BUNKERING HOSE



Construction:

Tube: Black, smooth, Nitrile synthetic rubber, suitable for up to 50% aromatic content

Reinforcement: Multiply heavy duty synthetic tire cord supported with helix wire, anti-static wires

Cover: Black, wrapped finish, synthetic rubber for high abrasion, ozone & weather resistance

Temperature:

-40°C to +100°C (+180°F)

Application:

Heavy duty suction and discharge dock hose designed for transferring petroleum product up to 50% aromatic content from tankers and barges, bunkering service and industrial applications.

Characteristic:

- C/W built-in flanges with one side fixed and one side swivel
- Heavy duty construction for 300psi
- Designed for petrol products up to 50% aromatic content
- High abrasion, ozone & weather resistant cover



Item	I.D.		O.D.	W.P.		B.P.		L	
	inch	mm	mm	bar	psi	bar	psi	m	ft
KDOT076	3"	76.2	96	20	300	60	900	61	200
KDOT100	4"	101.6	126	20	300	60	900	61	200
KDOT125	5"	127	155	20	300	60	900	30.5	100
KDOT150	6"	152.4	185	20	300	60	900	30.5	100
KDOT200	8"	203.2	242	20	300	60	900	11.8	39
KDOT250	10"	254	298	20	300	60	900	11.8	39