

NX FOUR SPIRAL WIRE HOSE

Exceeds the requirements of SAE 100R12 - EN856



- Tube:** Nitrile
- Reinforcement:** Four spirals of high tensile wire
- Cover:** Black, oil, abrasion and weather resistant synthetic rubber, MSHA approved
- Temperature:** 40°C to +121°C (-40°F to +250°F)
- Packaging:** Coils
- Application:** Hydraulic systems with petroleum or water/glycol based fluids and for fuel and lubricating oils.

Part No.	I.D.		O.D.		Max W.P. (psi)	Minimum Burst Pressure (psi)	Minimum Bend Radius		Weight (lbs/ft)	One Piece Non-Skive COUPLINGS	One Piece Skive COUPLINGS
	(in)	(mm)	(in)	(mm)			(in)	(mm)			
NX-06	3/8	0.79	20	5,000	20,000	5.0	127	0.40	N, V		
NX-08	1/2	0.94	24	5,000	20,000	7.0	178	0.54	N, V		
NX-10	5/8	1.06	27	5,000	20,000	8.0	203	0.74	N		
NX-12	3/4	1.26	32	5,000	20,000	9.5	241	0.89	N, V		
NX-16	1	1.50	38	5,500	22,000	12.0	305	1.30	N, V		
NX-20	1 1/4	1.81	46	5,000	20,000	16.5	419	1.79	N	VS	
NX-24	1 1/2	2.13	54	4,300	17,200	20.0	508	2.06	N	VS	
NX-32	2	2.68	68	3,600	14,400	25.0	635	2.78	N	VS	

Note: NX hose will be obsolete once inventory is depleted - NT300 hose is the replacement (see page 6).