

NZ FOUR SPIRAL WIRE HOSE

Meets or exceeds the requirements of SAE 100R12 - EN856



- Tube:** Nitrile
- Reinforcement:** Four spirals of high tensile steel
- Cover:** Black, oil, abrasion and weather resistant synthetic rubber, MSHA approved
- Temperature:** -40°C to +121°C (-40°F to +250°F)
- Packaging:** Coil length 200' continuous
- Application:** Hydraulic systems with petroleum or water/glycol based fluids and for fuel and lubricating oils.

Part No.	I.D.		O.D.		Max W.P. (psi)	Minimum Burst Pressure (psi)	Minimum Bend Radius		Weight (lbs/ft)	ONE PIECE Non-Skive	One Piece Skive
	(in)	(mm)	(in)	(mm)			(in)	(mm)		COUPLINGS	COUPLINGS
NZ-12	¾	19.0	1.26	32	6,100	24,400	11.0	280	1.03	N, V	
NZ-16	1	25.4	1.51	38.4	5,500	22,000	13.3	340	1.44	N, V	
NZ-20	1¼	31.8	1.78	45.2	5,000	20,000	18.1	460	1.68	N	VS
NZ-24	1½	38.1	2.09	53	4,300	17,200	22.0	560	2.24	N	VS
NZ-32	2	50.8	2.66	67.6	3,600	14,400	27.5	700	3.08	N	VS