

PE10 PETRO-FLEX CORRUGATED TANK TRUCK HOSE



Application: For use with petroleum based products with aromatic content up to 50%. An all purpose petroleum suction and discharge hose. For tank truck & in plant operations to transfer gasoline, kerosene, diesel, fats, grease, animal and vegetable oils - may also be used for hydraulic suction and return lines. Rated full vacuum.

Tube: Black smooth synthetic rubber compound
Reinforcement: Synthetic yarn with a double wire helix
Cover: Black corrugated
Temperature: -35°C to +100°C (-31°F to +212°F)

| Part No. | I.D. Inches | O.D. Inches | Max W.P. PSI | Bend Radius Inches | Weight (lbs./ft.) | Standard Lengths |
|----------|-------------|-------------|--------------|--------------------|-------------------|------------------|
| PE10-100 | 1 | 1.42 | 150 | 2.0 | 0.54 | 100' |
| PE10-125 | 1¼ | 1.70 | 150 | 2.5 | 0.67 | 100' |
| PE10-150 | 1½ | 1.95 | 150 | 3.0 | 0.84 | 100' |
| PE10-200 | 2 | 2.50 | 150 | 4.2 | 1.10 | 100'/200' |
| PE10-250 | 2½ | 3.03 | 150 | 5.0 | 1.41 | 100' |
| PE10-300 | 3 | 3.56 | 150 | 6.0 | 1.72 | 100'/200' |
| PE10-400 | 4 | 4.60 | 150 | 12.0 | 2.27 | 100'/200' |
| PE10-600 | 6 | 6.77 | 150 | 18.1 | 4.77 | 100'/200' |
| PE10-800 | 8 | 8.85 | 150 | 20.1 | 6.02 | 100' |