

# NZ Four Spiral Hose

Meets or exceeds the requirements of SAE 100R12 - EN856



- Tube: Nitrile
- Reinforcement: Four spirals of high tensile steel
- Cover: Black, oil, abrasion and weather resistant synthetic rubber, MSHA approved
- Temperature: -40°C to +121°C (-40°F to +250°F)
- Packaging: Coils
- Application: Hydraulic systems with petroleum or water/glycol based fluids. For fuel and lubricating oils.

PART NUMBER	HOSE I.D.	HOSE O.D.		MAXIMUM WORKING PRESSURE	MINIMUM BURST PRESSURE	MINIMUM BEND RADIUS		WEIGHT	ONE PIECE Non-Skive	ONE PIECE Skive
	(in)	(in)	(mm)	(psi)	(psi)	(in)	(mm)	(lbs/ft)	COUPLINGS	COUPLINGS
NZ-08	1/2	0.96	24.4	6,000	24,000	9.1	230	0.58	N, V	
NZ-12	3/4	1.26	32.0	6,100	24,400	11.0	280	1.03	N, V	
NZ-16	1	1.51	38.4	5,500	22,000	13.3	340	1.44	N, V	
NZ-20	1 1/4	1.78	45.2	5,000	20,000	18.1	460	1.68	N	
NZ-24	1 1/2	2.09	53.0	4,300	17,200	22.0	560	2.24	N	VS
NZ-32	2	2.66	67.6	3,600	14,400	27.5	700	3.08	N	VS