

## QC Four Spiral Hose (Half Bend)

Meets or exceeds the requirements of SAE 100R12 - EN856  
(Half the bend radius of SAE100R12)



- Tube: Seamless, black, oil and heat resistant synthetic rubber
- Reinforcement: Four spirals of high tensile wire
- Cover: Black, oil, abrasion and weather resistant synthetic rubber, MSHA approved
- Temperature: -40°C to +121°C (-40°F to +250°F)
- Packaging: Coils
- Application: Hydraulic systems with petroleum or water/glycol based fluids and for fuel and lubricating oils.

PART NUMBER	HOSE I.D.		HOSE O.D.		MAXIMUM WORKING PRESSURE (psi)	MINIMUM BURST PRESSURE (psi)	MINIMUM BEND RADIUS		WEIGHT (lbs/ft)	ONE PIECE Non-Skive	ONE PIECE Skive
	(in)	(in)	(in)	(mm)			(in)	(mm)		COUPLINGS	COUPLINGS
QC-06	3/8	0.80	20	20	4,000	16,000	2.5	64	.40	N, V	
QC-08	1/2	0.94	24	24	4,000	16,000	3.5	89	.54	N, V	
QC-10	5/8	1.08	27	27	4,000	16,000	4.0	102	.74	N	
QC-12	3/4	1.21	31	31	4,000	16,000	4.8	121	.94	N, V	
QC-16	1	1.50	38	38	4,000	16,000	6.0	153	1.34	N, V	
QC-20	1 1/4	1.85	47	47	3,000	12,000	8.3	210	1.74	N	VS
QC-24	1 1/2	2.10	53	53	2,500	10,000	10.0	254	2.01	N	VS
QC-32	2	2.63	67	67	2,500	10,000	12.5	318	2.75	N	VS

\* Hose can also be used with OEM reusable couplings.