

FSH 100R1 Red Fire Suppression Hose

Meets or exceeds the requirements of SAE 100R1 AT / DIN-EN 853 1SN



- Tube: Seamless, black, oil and heat resistant synthetic rubber
- Reinforcement: One wire braid of high tensile steel wire
- Cover: Red, oil abrasion and weather resistant synthetic rubber, MSHA approved
- Temperature: -40°C to +100°C (-40°F to +212°F)
- Packaging: Reels
- Application: Medium pressure hydraulic applications and fire suppression actuation equipment where the red cover allows for easy identification.

PART NUMBER	HOSE I.D.	HOSE O.D.		MAXIMUM WORKING PRESSURE (psi)	MINIMUM BURST PRESSURE (psi)	MINIMUM BEND RADIUS		WEIGHT (lbs/ft)	ONE PIECE
	(in)	(in)	(mm)			(in)	(mm)		COUPLINGS
FSH-04	¼	0.52	13.2	3,265	13,060	4.0	100	0.15	E
FSH-06	⅜	0.68	17.2	2,610	10,440	5.0	130	0.23	E
FSH-08	½	0.80	20.4	2,320	9,280	7.0	180	0.28	E
FSH-12	¾	1.08	27.5	1,525	6,100	9.5	240	0.40	E
FSH-16	1	1.39	35.4	1,275	5,100	12.0	300	0.59	E