

J3 Rubber Cover Push-On 300 PSI

- Tube: High oil resistant synthetic rubber
 Reinforcement: Synthetic Fiber
 Cover: Black, oil, abrasion and weather resistant synthetic rubber, MSHA approved
 Temperature: -40°C to +88°C (-40°F to + 190°F)
 Packaging: Reels
 Application: Petroleum based hydraulic fluids, gasoline, water, diesel fuels and lubricating oils



PART NUMBER	HOSE I.D.		HOSE O.D.		MAXIMUM WORKING PRESSURE	MINIMUM BURST PRESSURE	MINIMUM BEND RADIUS		WEIGHT	ONE PIECE COUPLINGS
	(in)	(mm)	(in)	(mm)			(in)	(mm)		
J3-04BK*	¼	6.35	0.54	13.7	300	1,200	3.0	64	0.09	J
J3-05BK*	⅜	9.52	0.62	15.7	300	1,200	3.0	76	0.12	J
J3-06BK*	½	12.7	0.69	17.5	300	1,200	3.0	76	0.14	J
J3-08BK*	¾	19.05	0.81	20.6	300	1,200	5.0	127	0.17	J
J3-10BK*	1	25.4	0.93	23.6	300	1,200	6.0	152	0.20	J
J3-12BK*	1 ¼	31.75	1.07	27.2	300	1,200	7.0	178	0.26	J
J3-16BK*	2	50.8	1.34	34.0	300	1,200	8.0	203	0.34	J

* BK indicates the color black, for other colors change the suffix to the following: BL - Blue, GY - Grey, GN - Green, RD - Red, BN - Brown, YW - Yellow or WH - White. Some colors are non-stock and may require minimum runs.