

TBX Convoluted Smooth Bore Teflon Stainless

- Tube:** Black non-leaching FDA compliant static conductive
Cover: One braid of 304 stainless steel wire
Temperature: -54°C to 232°C (-65°F to +450°F) Continuous service
 -73°C to +260°C (-100°F to +500°F) Intermittent service
Packaging: Random coils
Application: Steam, chemical, automotive, food processing,
 pharmaceutical and petroleum based hydraulic fluids



PART NUMBER	HOSE I.D.	HOSE O.D.		MAXIMUM WORKING PRESSURE	MINIMUM BEND RADIUS		WEIGHT	ONE PIECE Skive
	(in)	(in)	(mm)	(psi)	(in)	(mm)	(lbs/ft)	COUPLINGS
TBX-04C	¼	0.38	9.6	1280	0.8	19	0.06	T, TS
TBX-05C	⅜	0.42	10.6	1220	0.8	19	0.08	T, TS
TBX-06C	½	0.53	13.5	1160	1.0	25	0.10	T, TS
TBX-08C	¾	0.69	17.5	870	1.5	38	0.15	T, TS
TBX-10C	1	0.83	21.1	730	2.0	50	0.23	T, TS
TBX-12C	1½	0.95	24.2	610	2.5	63	0.26	T, TS
TBX-16C	2	1.25	31.7	580	3.0	75	0.36	T, TS

Note: Also available with Natural non-conductive PTFE Tube (Remove "C" at end of part number, ie TBX-04).