

AR10 GENERAL PURPOSE AIR/WATER 200



Application:

Air, water, agricultural spray solutions, and other diluted chemicals.
Good resistance to heat, abrasion, and weathering.

Construction:

Tube - Black, limited oil resistant synthetic rubber

Reinforcement - Synthetic yarn

Cover - Smooth red, abrasion, weather and ozone resistant rubber

Branding - FLEXTAL AR10-100 1" (25.4mm) GENERAL PURPOSE AIR/WATER 200 PSI MAX WP

Temperature Range:

-35°C to +80°C (-30°F to +180°F)

Part No.	I.D. Inches	O.D. Inches	Max W.P. PSI	Weight lbs / ft	EcoCoils	Reel Lengths
AR10-025	¼	0.50	200	0.11	300'	300',600'
AR10-031	5/16	0.58	200	0.14	300'	300',600'
AR10-038	3/8	0.67	200	0.18	300'	300',600'
AR10-050	½	0.81	200	0.24	300'	300',600'
AR10-063	5/8	0.97	200	0.32	300'	300'
AR10-075	¾	1.12	200	0.42	300'	300',500'
AR10-100	1	1.45	200	0.65	300'	300',400'
AR10-125	1¼	1.73	200	0.84	200'	200',400'
AR10-150	1½	2.09	200	1.24	200'	200',400'
AR10-200	2	2.60	200	1.62	200'	200',400'

*EcoCoil: Hose packaged in coils, not wound on a wooden or plastic reel.

AR10 GENERAL PURPOSE 200 ASSEMBLIES



Part No.	Hose Size	Fitting A	Fitting B	Length (ft.)	Attaching Method
AR10-025MM25	¼	¼ NPT	¼ NPT	25	Crimp
AR10-025MM50	¼	¼ NPT	¼ NPT	50	Crimp
AR10-038M2525M25	3/8	¼ NPT	¼ NPT	25	Crimp
AR10-038M2525M50	3/8	¼ NPT	¼ NPT	50	Crimp
AR10-038M2525M100	3/8	¼ NPT	¼ NPT	100	Crimp
AR10-038MM50	3/8	3/8 NPT	3/8 NPT	50	Crimp
AR10-038MM100	3/8	3/8 NPT	3/8 NPT	100	Crimp
AR10-050MM50	½	½ NPT	½ NPT	50	Crimp
AR10-075UUX50	¾	Universal	Universal	50	Crimp
AR10-075UUX100	¾	Universal	Universal	100	Crimp
AR10-100UUX50	1	Universal	Universal	50	Crimp
AR10-100UUX100	1	Universal	Universal	100	Crimp

*Call for other lengths and fitting combinations.