

AR11 CONTRACTORS WATER



Application:

For a wide range of heavy duty industrial, construction, and agricultural water discharge applications in which a heavy duty rubber water hose is needed.

Construction:

Tube - Black, limited oil resistant synthetic rubber

Reinforcement - Synthetic yarn

Cover - Smooth black, abrasion, and weather resistant rubber

Branding - FLEXTRAL AR11-100 1" (25.4mm) GENERAL PURPOSE
AIR/WATER 200 PSI MAX WP

Temperature Range:

-35°C to +80°C (-30°F to +180°F)

Part No.	I.D. Inches	O.D. Inches	Max W.P. PSI	Weight lbs / ft	EcoCoils	Reel Lengths
AR11-025	1/4	0.50	200	0.09	300'	300'/600'
AR11-031	5/16	0.58	200	0.12	300'	300'/600'
AR11-038	3/8	0.67	200	0.15	300'	300'/600'
AR11-050	1/2	0.81	200	0.20	300'	300'/600'
AR11-063	5/8	0.97	200	0.27	300'	300'
AR11-075	3/4	1.12	200	0.34	300'	300'/500'
AR11-100	1	1.44	200	0.54	300'	300'/400'
AR11-125	1 1/4	1.73	200	0.75	200'	200'/400'
AR11-150	1 1/2	1.98	200	0.86	200'	200'/400'

*EcoCoil: Hose packaged in coils, not wound on a wooden or plastic reel.

AR11 CONTRACTORS WATER ASSEMBLIES



Part No.	Hose Size	Fitting A	Fitting B	Length (ft)	Attaching Method
AR11-050GHT25	1/2	M-GHT	F-GHT	25	Crimp
AR11-050GHT50	1/2	M-GHT	F-GHT	50	Crimp
AR11-050GHT75	1/2	M-GHT	F-GHT	75	Crimp
AR11-050GHT100	1/2	M-GHT	F-GHT	100	Crimp
AR11-063GHT25	5/8	M-GHT	F-GHT	25	Crimp
AR11-063GHT50	5/8	M-GHT	F-GHT	50	Crimp
AR11-063GHT75	5/8	M-GHT	F-GHT	75	Crimp
AR11-063GHT100	5/8	M-GHT	F-GHT	100	Crimp
AR11-075GHT25	3/4	M-GHT	F-GHT	25	Crimp
AR11-075GHT50	3/4	M-GHT	F-GHT	50	Crimp
AR11-075GHT75	3/4	M-GHT	F-GHT	75	Crimp
AR11-075GHT100	3/4	M-GHT	F-GHT	100	Crimp

*Call for other lengths and fitting combinations.