

AR20 GENERAL PURPOSE AIR/WATER 300



Application:

Air, water, agricultural spray solutions, and other diluted chemicals. High resistance to heat, abrasion, and weathering.

Construction:

Tube - Black, limited oil resistant synthetic rubber

Reinforcement - Synthetic yarn

Cover - Smooth red, abrasion, weather and ozone resistant rubber

Branding - FLEXTRAL AR20-100 1" (25.4mm) GENERAL PURPOSE AIR/WATER 300 PSI MAX WP

Temperature Range:

-35°C to +80°C (-30°F to +180°F)

Part No.	I.D. Inches	O.D. Inches	Max W.P. PSI	Weight lbs / ft	EcoCoils	Reel Lengths
AR20-025	¼	0.53	300	0.13	300'	300',600'
AR20-038	⅜	0.70	300	0.21	300'	300',600'
AR20-050	½	0.84	300	0.27	300'	300',600'
AR20-063	⅝	0.98	300	0.34	300'	300'
AR20-075	¾	1.15	300	0.46	300'	300',500'
AR20-100	1	1.47	300	0.68	300'	300',400'
AR20-125	1¼	1.73	300	0.84	300'	200',400'
AR20-150	1½	2.09	300	1.24	300'	200',400'
AR20-200	2	2.64	300	1.74	300'	200',400'

*EcoCoil: Hose packaged in coils, not wound on a wooden or plastic reel.

AR20 GENERAL PURPOSE 300 ASSEMBLIES



Part No.	Hose Size	Fitting A	Fitting B	Length (ft.)	Attaching Method
AR20-025MM25	¼	¼ NPT	¼ NPT	25	Crimp
AR20-025MM50	¼	¼ NPT	¼ NPT	50	Crimp
AR20-038M2525M25	⅜	¼ NPT	¼ NPT	25	Crimp
AR20-038M2525M50	⅜	¼ NPT	¼ NPT	50	Crimp
AR20-038M2525M100	⅜	¼ NPT	¼ NPT	100	Crimp
AR20-038MM25	⅜	⅜ NPT	⅜ NPT	25	Crimp
AR20-038MM50	⅜	⅜ NPT	⅜ NPT	50	Crimp
AR20-038MM100	⅜	⅜ NPT	⅜ NPT	100	Crimp

*Call for other lengths and fitting combinations.