

## AR55 RECOIL HOSE ASSEMBLIES



**Application:**

Self storing, coiled tube assemblies. Air lines for assembly applications. Suitable for low temperature. Automotive repair, body shops, car wash, carwash soap applications. Pneumatic airlines on machinery. Manufacturing air tool lines. Suitable for water, fluids, and some chemicals.  
 \*Not suitable for brake fluids.

**Construction:**

**Tube/Cover** - Ether based polyurethane

**Fittings** - Permanently crimped male brass swivel NPT ends. Bend restrictors over fittings prevents scratches and scuffs.

**Temperature Range:**

-40°C to +79°C (-40°F to +175°F)

Part No.	I.D. Inches	O.D. Inches	Max W.P. PSI (70° F)	Max W.P. PSI (122° F)	Weight lbs / ea.
AR55-025-10	1/4	0.38	125 PSI	75 PSI	0.50
AR55-025-15	1/4	0.38	125 PSI	75 PSI	0.65
AR55-025-20	1/4	0.38	125 PSI	75 PSI	0.65
AR55-025-25	1/4	0.38	125 PSI	75 PSI	0.85
AR55-025-30	1/4	0.38	125 PSI	75 PSI	1.20
AR55-025-50	1/4	0.38	125 PSI	75 PSI	2.00
AR55-038-10	3/8	0.57	125 PSI	75 PSI	1.00
AR55-038-15	3/8	0.57	125 PSI	75 PSI	1.40
AR55-038-20	3/8	0.57	125 PSI	75 PSI	1.80
AR55-038-25	3/8	0.57	125 PSI	75 PSI	2.20
AR55-038-30	3/8	0.57	125 PSI	75 PSI	2.40
AR55-038-50	3/8	0.57	125 PSI	75 PSI	4.00