

## AR67 CONTRACTORS 300 AIR



**Application:**

For construction, mining, and industrial use.

**Construction:**

**Tube** - Oil mist resistant black synthetic rubber

**Reinforcement** - Synthetic yarn

**Cover** - Yellow abrasion resistant rubber with green stripe

**Branding** - FLEXTRAL AR67-100 1" CONTRACTORS AIR/WATER  
300 PSI MAX WP

**Temperature Range:**

-30°C to +82°C (-30°F to +180°F)

Part No.	I.D. Inches	O.D. Inches	Max W.P. PSI	Weight (lbs / ft)	Standard Lengths
AR67-050	1/2	0.91	300	0.25	50'/100'
AR67-075	3/4	1.18	300	0.40	50'/100'
AR67-100	1	1.46	300	0.50	50'/100'
AR67-125	1 1/4	1.73	300	0.73	50'/100'
AR67-150	1 1/2	2.05	300	0.93	50'/100'
AR67-200	2	2.63	300	1.16	50'/100'
AR67-250	2 1/2	3.11	300	1.55	50'/100'
AR67-300	3	3.62	300	1.86	50'/100'

## AR67 CONTRACTORS 300 AIR ASSEMBLIES



Part No.	Hose Size	Fitting A	Fitting B	Length (ft)	Attaching Method
AR67-075UUX50	3/4	Universal	Universal	50	Crimp
AR67-075FFX50	3/4	Female G-J	Female G-J	50	Crimp
AR67-200FFX50	2	Female G-J	Female G-J	50	Crimp
AR67-075FFBC50	3/4	Female G-J	Female G-J	50	Bolt Clamp
AR67-200FFBC50	2	Female G-J	Female G-J	50	Bolt Clamp
AR67-050MHMHX50	1/2	Mine Fitting	Mine Fitting	50	Crimp
AR67-100MHMHX50	1	Mine Fitting	Mine Fitting	50	Crimp
AR67-075QMOMX50	3/4	Dix-Lok	Dix-Lok	50	Crimp

\*Call for other lengths and fitting combinations.