

CP22 HD MARINE COMPO CHEM HOSE PG



Application:

FLEXTRAL CP22 HD MARINE is an heavy duty hose for the transfer of a wide variety of chemicals under suction or pressure. FLEXTRAL CP22 hoses are used for ship to shore and ship to ship, dockside and general shipboard use. All hoses are 100% aromatic resistant, antistatic and can be used for suction or discharge.

FLEXTRAL CP22 HD MARINE hose is manufactured according to the requirement specified by the European Standards EN 13765:2010 Type 3 (BS 5842:1980), and in accordance with the recommendations of NAHAD Guidelines (NAHAD 600/2005). DNV and Rina approved. Meets USCG requirements.

Construction:

FLEXTRAL CP22 HD MARINE hose is a multi-layer thermoplastic hose manufactured with extra Polypropylene, Polyethylene, Polyester films and Polypropylene fabrics, with a weather-proof and abrasion resistant outer cover made of Polymeric coated Polyester fabric. All the different layers are wrapped together and tensioned between polypropylene coated galvanized internal and galvanized external wire spirals of bigger diameter and higher density. This enables our product to maintain extreme flexibility with tremendous strength and durability.

Branding - FLEXTRAL CP22-1200 12" HD COMPO CARGO & OIL HOSE 200 PSI MAX WP PG

Temperature Range:

-40°C to +100°C (-40°F to +212°F)

| Part No. | I.D. Inches | Max W.P. PSI | Bend Radius Inches | Weight (lbs./ft.) | Standard Lengths |
|-----------|-------------|--------------|--------------------|-------------------|------------------|
| CP22-600 | 6 | 200 | 23 | 6.46 | 130' |
| CP22-800 | 8 | 200 | 32 | 8.93 | 130' |
| CP22-1000 | 10 | 200 | 40 | 14.31 | 80' |
| CP22-1200 | 12 | 200 | 48 | 21.28 | 80' |

*Other wire variations available upon request.

**See pages 106-109 for fittings and accessories that are readily available.