

J4 RUBBER COVER PREMIUM PUSH-ON HOSE 350 PSI

**Application:**

Petroleum based hydraulic fluid, diesel fuel, lubrication oil, gasoline, air, water, and antifreeze coolants.

Construction:

Tube: High oil resistant synthetic rubber - RMA class A (high oil resistance)

Reinforcement: Synthetic fiber

Cover: Synthetic rubber, oil, abrasion, and UV resistant; MSHA approved

Branding: FLEXTRAL GRIP-LOC J4-12 3/4" 350 PSI MAX WP

Temperature: Oil/Air: -40°C to +125°C (-40°F to +257°F)

Water: +100°C (+212°F)

Part No.	I.D. Inches	O.D. Inches	Max W.P. PSI	Weight (lbs / ft)	Reel Lengths
J4-04BK*	1/4	0.48	350	0.09	350'
J4-05BK*	5/16	0.55	350	0.12	350'
J4-06BK*	3/8	0.63	350	0.14	350'
J4-08BK*	1/2	0.75	300	0.17	350'
J4-10BK*	5/8	0.91	300	0.20	350'
J4-12BK*	3/4	1.03	300	0.26	350'

*BK indicates the color black, for other colors change the suffix to the following: BL - Blue, GY - Grey, GN - Green, RD - Red
*BN - Brown, YW - Yellow or WH - White. Some colors are non-stock and may require minimum runs.