

## CX 100R15 SIX SPIRAL WIRE HOSE



Meets or exceeds the requirements of SAE 100R15

- Tube:** Nitrile
- Reinforcement:** Six spiral layers of high tensile steel wire
- Cover:** Black, oil, abrasion and weather resistant synthetic rubber, MSHA approved
- Temperature:** -40°C to +121°C (-40°F to +250°F)
- Packaging:** Coils
- Application:** Hydraulic systems with petroleum or water/glycol based fluids and for fuel and lubricating oils.

Part No.	I.D.		O.D.		Max W.P. (psi)	Minimum Burst Pressure (psi)	Minimum Bend Radius		Weight (lbs/ft)	ONE PIECE Non-Skive	Two Piece Skive
	(in)	(mm)	(in)	(mm)			(in)	(mm)		COUPLINGS	COUPLINGS
CX-06	3/8	17.5	0.69	17.5	6,000	24,000	6.0	150	0.51	V	
CX-08	1/2	20.2	0.80	20.2	6,000	24,000	8.0	200	0.59	V	
CX-12	3/4	30.7	1.20	30.7	6,000	24,000	11.0	280	1.09	V	
CX-16	1	38.7	1.52	38.7	6,000	24,000	11.8	300	1.46	V	
CX-20	1 1/4	50.0	1.97	50.0	6,000	24,000	15.7	400	2.40		VS
CX-24	1 1/2	57.6	2.27	57.6	6,000	24,000	19.7	500	3.02		VS
CX-32	2	75.0	2.95	75.0	6,000	24,000	23.6	600	5.05		C

\* C32 is a two-piece external skive only coupling.