

NT300 FOUR SPIRAL WIRE HOSE

Exceeds the requirements of SAE 100R12 - EN856



- Tube:** Nitrile
Reinforcement: Four spirals of high tensile wire
Cover: Synthetic rubber, high abrasion resistant, meets requirements of MSHA fire resistance standards
Temperature: -54°C to +121°C (-65°F to +250°F)
Packaging: Coils
Application: Extremely flexible with a bend radius less than standard spiral hose and has a high abrasion resistant cover. NT300 is ideal for hydraulic systems with petroleum, polyol ester, or water/glycol based fluids. Hose is USCG accepted for hydraulic service.

Part No.	I.D.		O.D.		Max W.P. (psi)	Minimum Burst Pressure (psi)	Minimum Bend Radius		Weight (lbs/ft)	One Piece Non-Skive COUPLINGS	One Piece Skive COUPLINGS
	(in)	(in)	(mm)	(mm)			(in)	(mm)			
NT300-06	3/8	0.83	21.0		6,000	24,000	4.9	125	0.42	N, V	
NT300-08	1/2	0.90	22.8		5,000	20,000	4.3	110	0.46	N, V	
NT300-10	5/8	1.06	25.8		5,000	20,000	5.5	140	0.64	N	
NT300-12	3/4	1.17	29.8		5,000	20,000	6.7	170	0.68	N, V	
NT300-16	1	1.49	37.8		5,500	22,000	8.7	220	1.25	N, V	
NT300-20	1 1/4	1.80	45.6		5,000	20,000	15.0	380	1.55	N	VS
NT300-24	1 1/2	2.06	52.4		4,300	17,200	17.7	450	1.86	N	VS
NT300-32	2	2.65	67.3		3,600	14,400	19.7	500	2.97	N	VS