

RIG FLOW 5000 SLIM HOLE ROTARY DRILL HOSE



- Tube:** Nitrile
Reinforcement: Four spirals of high tensile steel
Cover: Black, oil, abrasion and weather resistant synthetic rubber, MSHA approved
Temperature: -40°C to +121°C (-40°F to +250°F)
Application: High-pressure rotary hose for slim-hole, seismograph, work-over or portable drilling rigs. For use with small to medium-blast, water-well or shot-hole drilling applications. Used in hydraulic oil, mud or where pulsating pump is required.

| Part No. | I.D. | | O.D. | | Max W.P. (psi) | Minimum Burst Pressure (psi) | Minimum Bend Radius | | Weight (lbs/ft) | Two Piece Skive COUPLINGS |
|-----------|------|------|------|------|-------------------|---------------------------------|---------------------|------|--------------------|------------------------------|
| | (in) | (mm) | (in) | (mm) | | | (in) | (mm) | | |
| RF5000-32 | 2 | 49.3 | 1.94 | 49.3 | 5,000 | 14,800 | 16.5 | 420 | 2.45 | BSS |
| RF5000-40 | 2½ | 63.5 | 3.35 | 85.2 | 5,000 | 15,000 | 26.0 | 660 | 5.13 | BSS |